

AKUSTIK® - GIPS ART. 4 (Pb)

MATERIAL

Akustik®- Gips Art. 4 is a plasterboard with a lead layer coating on one side whose thickness can go from 0.5 to 4 mm. This product is used for the screening treatment of walls and ceilings of X-ray rooms, in order to avoid the propagation of waves. Akustik® k -Gips Art. 4 is also a good sound-insulating material.

DIMENSIONS

Width: 1200 mm

Length: 1000 - 2000 mm

FIELDS OF APPLICATION

Surgeries, hospitals, etc.

INSTALLATION

Akustik® k -Gips Art. 4 must be installed as a normal plasterboard, taking great care over joints and screws sealing by a lead sheet strip (PB-BAND) to have a total screening. The second plasterboard will be fixed through a specific adhesive mortar without screws.

PLASTERBOARD WITH A LEAD SHEET LAYER COATING ON ONE SIDE FOR THE SCREENING OF X-RAY ROOMS

CE MARKED PRODUCT



COMPOSITION

	5/10 BA 12,5	5,8 Kg circa
	10/10 BA 12,5	11,5 Kg circa
	15/10 BA 12,5	16 Kg circa
	20/10 BA 12,5	22 Kg circa
	30/10 BA 12,5	34 Kg circa

Schema di montaggio dall'alto

