

Ampacoll® Fenax

Window connection tape



- > Extremely adhesive
- > Full-surface adhesive
- > Moisture variable
- > One and the same tape can be used inside and outside. The "tighter inside than outside" requirement is met.
- > Easy-peel liner
- > Safe to plaster over

Technical details		Value	Standard
S _d value		1.5–16.5m	
Amount of adhesive to be applied		300g/m ²	
Application temperature		–5 °C to +40 °C	
Temperature resistance		–40 °C to +100 °C	
UV stability		12 months (Central Europe)	
Tear resistance	lengthwise	220N/5 cm	EN 12311-2/A
	cross	280N/5 cm	
Elongation at break	lengthwise	100%	EN 12311-2/A
	cross	140%	




Joint properties as per ift
guideline MO01/1:
2007 – Section 5
18_002878_PRO3
(PB_E03_020310-en)





Area of application: For sealing doors and windows in solid, wood and metal constructions **after** installation.

Delivery forms				
Item no.	Identification	Roll size	Box contents	Pallet contents
7640115537331	Ampacoll® Fenax 12/63	25 m × 75 mm Liner division: 12 mm, 63 mm	6 rolls = 150 metres	72 boxes
7640115537775	Ampacoll® Fenax 75	25 m × 75 mm	6 rolls = 150 metres	72 boxes
7640115537362	Ampacoll® Fenax 12/88	25 m × 100 mm Liner division: 12 mm, 88 mm	4 rolls = 100 metres	72 boxes
7640115536921	Ampacoll® Fenax 40/60	25 m × 100 mm Liner division: 40 mm, 60 mm	4 rolls = 100 metres	72 boxes
7640115537836	Ampacoll® Fenax 100	25 m × 100 mm	4 rolls = 100 metres	72 boxes
7640115537393	Ampacoll® Fenax 12/138	25 m × 150 mm Liner division: 12 mm, 138 mm	2 rolls = 50 metres	72 boxes



 Please observe our installation instructions for our window products.

 Please observe the recommendations for use and further system products in our adhesives matrix.

 Further information and detailed documentation at www.ampack.biz

Sales via specialist dealers

Ampack Swiss: 071 858 38 00
Ampack Austria: 05523 53433
Ampack Germany: 07621 1610264
Ampack France: 04 50 83 70 54
Ampack Italy: 0471 053 475

www.ampack.biz



The following information may have been superseded by new findings or developments.
Current information can be found at www.ampack.biz. © Ampack AG, Rorschach, 05.2019

8005EU/DX.YY(VS)0519